

View Online at <https://aerobasegroup.com/nsn/4720-00-274-7924>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Outside Diameter:

0.438 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

1600.0 pounds per square inch

Layer Composition And Location:

2nd layer woven polyester fiber cord and outer layer woven polyamide cord and 1st layer woven cotton cord

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

650.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches

Special Features:

Lacquer coated hose

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0