## NSN 4720-00-274-7924

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-274-7924 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Outside Diameter:** 0.438 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 24 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** 2nd layer woven polyester fiber cord and outer layer woven polyamide cord and 1st layer woven cotton cord Thread Size: 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 650.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 10.000 inches **Special Features:** Lacquer coated hose Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** 

N/a

Uns 1st end Shelf Life:

## NSN 4720-00-274-7924

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0