

View Online at <https://aerobasegroup.com/nsn/4720-00-274-8052>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Outside Diameter:

0.438 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

2nd layer spirally wrapped fabric and outer layer braided polyester cord and 1st layer spirally wrapped cotton fabric

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

800.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.250 inches

Special Features:

Lacquer coated hose

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0