## NSN 4720-00-274-8226

**Cross Sectional Shape:** 

Thread Direction:
Right-hand 1st end
Inside Diameter:

**Tempurature Rating:** 

**Outside Diameter:** 

0.250 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-274-8226

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

0.593 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Nonskive
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
27.500 inches
Media For Which Designed:
Hydraulic fluid, silicate-ester base single response
Thread Series Designator:
Nptf 1st end

## NSN 4720-00-274-8226

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0