## NSN 4720-00-274-9274

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-274-9274

Cross Sectional Shape:  Round  Thread Class:  3b 1st end  Thread Direction:  Right-hand 1st end  Inside Diameter:  0.188 inches  Tempurature Rating:  -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter:  0.515 inches  Minimum Inside Bending Radius:  3.000 inches  Connection Style:  Swivel nut flare 1st end  End Connection Design:
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.515 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut flare 1st end
Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.515 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut flare 1st end
Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.515 inches Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut flare 1st end
Right-hand 1st end  Inside Diameter:  0.188 inches  Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter: 0.515 inches  Minimum Inside Bending Radius: 3.000 inches  Connection Style: Swivel nut flare 1st end
Inside Diameter:  0.188 inches  Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter:  0.515 inches  Minimum Inside Bending Radius:  3.000 inches  Connection Style:  Swivel nut flare 1st end
0.188 inches  Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter: 0.515 inches  Minimum Inside Bending Radius: 3.000 inches  Connection Style:  Swivel nut flare 1st end
Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter: 0.515 inches  Minimum Inside Bending Radius: 3.000 inches  Connection Style: Swivel nut flare 1st end
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  Outside Diameter:  0.515 inches  Minimum Inside Bending Radius:  3.000 inches  Connection Style:  Swivel nut flare 1st end
Outside Diameter:  0.515 inches  Minimum Inside Bending Radius:  3.000 inches  Connection Style:  Swivel nut flare 1st end
0.515 inches  Minimum Inside Bending Radius: 3.000 inches  Connection Style: Swivel nut flare 1st end
Minimum Inside Bending Radius: 3.000 inches Connection Style: Swivel nut flare 1st end
3.000 inches  Connection Style:  Swivel nut flare 1st end
Connection Style: Swivel nut flare 1st end
Swivel nut flare 1st end
End Connection Design.
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth  Macauring Mathed And Length:
Measuring Method And Length:
40.500 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response  Thread Series Designator:

Unjf 1st end

## NSN 4720-00-274-9274

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

96906-ms28741 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0