NSN 4720-00-274-9335

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-274-9335 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Outside Diameter:** 0.766 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Mildew resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.000 inches working **Special Markings:** Date of mfr Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:**

Unf 1st end

Shelf Life:

N/a

NSN 4720-00-274-9335

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0