

View Online at <https://aerobasegroup.com/nsn/4720-00-274-9522>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Outside Diameter:

0.516 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.125 inches working

Special Markings:

Date of mfr

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0