## NSN 4720-00-275-7772

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-275-7772

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.555 inches and 0.587 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Outside Diameter:	
1.031 inches	
Minimum Inside Bending Radius:	
6.500 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.875 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
24.000 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unif 1ct and	

Unjf 1st end

## NSN 4720-00-275-7772

Nonmetallic Hose Assembly - Page 2 of 2



Sı	pecif	icati	on Da	ta:
----	-------	-------	-------	-----

96906-ms28762 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0