Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-275-9469

Cr	oss Sectional Shape:
Ro	bund
Th	nread Class:
3b	o 1st end
Th	nread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.1	188 inches
Те	empurature Rating:
-6	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Οι	utside Diameter:
0.3	312 inches
Mi	inimum Inside Bending Radius:
2.0	000 inches
Ex	tterior Color:
Na	atural
Ar	ngle Between Rigid Elbow Fittings In Deg:
17	70.0
Co	onnection Style:
Sv	vivel nut flare 2nd end
Er	nd Connection Design:
Ell	bow 2nd end
Co	onnection Type:
Th	areaded internal tube 1st end
Вι	urst Test Pressure:
60	00.0 pounds per square inch
La	ever Composition And Location:
Οι	uter layer braided corrosion resistant steel wire
Ма	aximum Operating Pressure:
15	00.0 pounds per square inch
Th	nread Size:
0.4	438 inches 1st end
Se	eat Angle:
37	0 degrees 2nd end
Ну	/drostatic Test Pressure:
30	00.0 pounds per square inch
Fle	ow Angle:
90	0.0 degrees 2nd end
Va	acuum In Torr:
50	0.8
In	side Surface Condition:
Sr	nooth



Measuring Method And Length:

32.000 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0