

View Online at <https://aerobasegroup.com/nsn/4720-00-277-8988>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.312 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.670 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer braided textile yarn and 1st layer braided textile yarn

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0