

View Online at <https://aerobasegroup.com/nsn/4720-00-278-1323>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.313 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.672 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

Grumman; a10 aircraft

**Burst Test Pressure:**

9000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord err-100

**Maximum Operating Pressure:**

2000.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and water resistant

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81349-mil-h-8794 government specification

**Specification Or Standard:**

6 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-8794 spec.