## NSN 4720-00-283-1920



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-283-1920 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.890 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** External seat for gasket seal (boss) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external boss 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded polyurethane and 1st layer braided synthetic cord **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.750 inches 1st end **Hydrostatic Test Pressure:** 7000.0 pounds per square inch **Outer Covering Environmental Protection:** Hydraulic solution resistant and weatherproof **Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

50.000 inches

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-00-283-1920

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0