Nonmetallic Hose Assembly - Page 1 of 2



Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-00-283-1921
Cross Sectional Shape: Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
<b>Tempurature Rating:</b> -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.890 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external boss 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded polyurethane and 1st layer braided synthetic cord
Maximum Operating Pressure:
3500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
54.000 inches
Thread Series Designator:
Unf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

