Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-285-6129

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| Between 0.367 inches and 0.391 inches  |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                              |
| Outside Diameter:  |
| Between 0.580 inches and 0.660 inches  |
| Minimum Inside Bending Radius:   |
| 3.000 inches   |
| Exterior Color:  |
| Black  |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Internal support   |
| Thready Qty Per Inch (tpi):  |
| 18 1st end   |
| Burst Test Pressure:   |
| 1500.0 pounds per square inch  |
| Layer Composition And Location:  |
| Outer layer molded rubber, chloroprene and 1st layer braided rayon cord                            |
| Maximum Operating Pressure:  |
| 250.0 pounds per square inch   |
| Thread Size:   |
| 0.562 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 500.0 pounds per square inch   |
| Outer Covering Environmental Protection:   |
| Abrasion resistant and oil resistant and ozone resistant and alcohol resistant and water resistant |
| Inside Curface Condition.  |

## Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 51.000 inches and 53.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon and water single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig:

A542a0