NSN 4720-00-286-0714

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-286-0714

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 420.0 degrees fahrenheit single response
Outside Diameter:
0.313 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Aircraft, eagle f-15
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
300.0 pounds per square inch
Maximum Operating Pressure:
50.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Fire resistant

Smooth

Measuring Method And Length:

Inside Surface Condition:

10.130 inches working

NSN 4720-00-286-0714

Nonmetallic Hose Assembly - Page 2 of 2



Р	r٥	di	uct	ł N	laı	me	١.

Hose assembly, nonmetallic-jet fuel starter fuel inlet

Special Features:

1st layer braided corrosion resistant steel wire outer layer braided corn, non-asbestos

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 50599 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0