## NSN 4720-00-288-8513

Nonmetallic Hose Assembly - Page 1 of 2



Tremmetame Floor Accessory Trage For E
View Online at https://aerobasegroup.com/nsn/4720-00-288-8513
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
320.0 degrees fahrenheit single response
Outside Diameter:
1.875 inches
Unable To Decode:
Unable to decode or unable to decode
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal hose 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
875.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally wrapped fabric
Maximum Operating Pressure:
75.0 pounds per square inch
Thread Size:

1.000 inches 2nd end

**Hydrostatic Test Pressure:** 

400.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Fire retardant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

600.000 inches excluding end fittings

**Second End Swivel Action Capability:** 

Not included

## NSN 4720-00-288-8513

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Inner conveying tube material-rubber, natural or rubber, synthetic

Media For Which Designed:

Steam single response

**Thread Series Designator:** 

Npsh 2nd end

**Specification Data:** 

81348-zz-h-541 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0