

View Online at <https://aerobasegroup.com/nsn/4720-00-288-9541>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

158.0 degrees fahrenheit single response

Outside Diameter:

1.375 inches

Hose Or Tubing Specification/std Data:

Fed zz-h-601 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Plain optional end 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal pipe 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided cotton cord

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

1.000 inches 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Special Markings:

W/date of mfr, water

Media For Which Designed:

Water, fresh single response

Thread Series Designator:

Npt 1st end

Specification Data:

Fed zz-h-601 professional/industrial association specification and 81348-zz-h-601 government specification

Specification Or Standard:

1 grade and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0