

View Online at <https://aerobasegroup.com/nsn/4720-00-288-9840>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.310 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.680 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

Mrap buffalo mk2a2

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

9000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer rubber impregnated braided fabric and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric

**Maximum Operating Pressure:**

2250.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81343-sae j517, 100r5 professional/industrial association standard

**Specification Or Standard:**

6 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541z0