NSN 4720-00-288-9870

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-288-9870

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.620 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.080 inches |
| Minimum Inside Bending Radius: |
| 6.500 inches |
| End Application: |
| Grumman a10 aircraft |
| Burst Test Pressure: |
| 6000.0 pounds per square inch single response |
| Layer Composition And Location: |
| 1st layer braided textile yarn err-100 |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch single response |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Material: |
| Rubber synthetic tube |
| Media For Which Designed: |
| Air single response and fuel/oil, hydrocarbon single response and water, fresh single response and water, salt single response |
| Specification Data: |
| 81343-sae j517, 100r5 professional/industrial association standard |
| Specification Or Standard: |
| 12 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541z0 |
| |