

View Online at <https://aerobasegroup.com/nsn/4720-00-289-1408>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

4.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal hose 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

1st layer molded rubber, chloroprene

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

4.000 inches 2nd end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and light resistant and oil resistant and oxidation resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nh-spcl 1st end

Specification Data:

81349-mil-h-71505 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0