

View Online at <https://aerobasegroup.com/nsn/4720-00-289-2645>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

4.000 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Hose Or Tubing Specification/std Data:**

Zz-h-561, gradea, type 1, style b, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Ww-c-621, type1, class aa specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Second End Fitting Specification/std Data:**

Ww-c-624, type b, style 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded internal hose 1st end

**Second End Relationship With First End:**

Not identical

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer rubber impregnated fabric

**Thread Size:**

4.000 inches 2nd end

**Hydrostatic Test Pressure:**

100.0 pounds per square inch

**Outer Covering Environmental Protection:**

Light resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

240.000 inches excluding end fittings

**Second End Swivel Action Capability:**

**Media For Which Designed:**

Water, fresh single response

**Thread Series Designator:**

Nh-spcl 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0