

View Online at <https://aerobasegroup.com/nsn/4720-00-289-3429>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.380 inches

End Application:

Virginia class cgn (41), los angeles class ssn (688), forrestal class cv, spruance class dd (963), arleigh burke class ddg, kidd class ddg, ticonderoga class cg (47), sturgeon class ssn (637), nimitz class cvn.

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

800.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber

Thread Size:

0.375 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches excluding end fittings

Special Features:

Weapon system essential; additional media for which designed: dope, mulsions, solvents

Special Markings:

Spray

Thread Series Designator:

Npsc 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0