

View Online at <https://aerobasegroup.com/nsn/4720-00-289-4253>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Outside Diameter:

0.437 inches

Unable To Decode:

Unable to decode or unable to decode

Exterior Color:

Green

First End Fitting Specification/std Data:

Mil ms15011, pc. No. 4 and pc. No. 5 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, gas 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber

Thread Size:

0.562 inches 1st end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches excluding end fittings

Seat Radius:

0.196 inches 1st end

Special Features:

Inner conveying tube material-rubber, buna-n or chloroprene

Special Markings:

Oxygen

Media For Which Designed:

Oxygen, gaseous single response

Thread Series Designator:

Unf 1st end

Specification Data:

Mil ms15011, pc. No. 4 and pc. No. 5 national std/spec

Specification Or Standard:

Yle a style

Departure From Cited Document:

As modified by material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0