NSN 4720-00-289-4256

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-4256

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.437 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Red
Connection Style:
Swivel nut, gas 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated polyamide fabric and 2nd layer rubber impregnated
braided cotton cord or 2nd layer rubber impregnated polyamide fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Light resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
120.000 inches excluding end fittings
Seat Radius:
0.196 inches 1st end

Acet-hyd

Special Markings:

NSN 4720-00-289-4256

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Acetylene single response
Thread Series Designator:
Unf 1st end
Specification Data:
81348-zz-h-461 government specification
Specification Or Standard:
A style
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0