

View Online at <https://aerobasegroup.com/nsn/4720-00-289-4256>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.437 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Red

Connection Style:

Swivel nut, gas 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated polyamide fabric and 2nd layer rubber impregnated braided cotton cord or 2nd layer rubber impregnated polyamide fabric and outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Light resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches excluding end fittings

Seat Radius:

0.196 inches 1st end

Special Markings:

Acet-hyd

Media For Which Designed:

Acetylene single response

Thread Series Designator:

Unf 1st end

Specification Data:

81348-zz-h-461 government specification

Specification Or Standard:

A style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0