## NSN 4720-00-289-4258

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-4258

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Left-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response
Outside Diameter:
0.594 inches
Exterior Color:
Red
Connection Style:
Swivel nut, gas 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated polyamide fabric and 2nd layer rubber impregnated
braided cotton cord or 2nd layer rubber impregnated polyamide fabric and outer layer molded rubber, synthetic
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches excluding end fittings
Seat Radius:
0.196 inches 1st end
Special Features:
Double braid; fitting designations (nut) cgae1hn023-000b; (tailpiece) cgae1ts022-d05b
Special Markings:
Capital letters/fuel/
Media For Which Designed:

Acetylene single response

## NSN 4720-00-289-4258

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Specification Or Standard:
S type and r grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0