

View Online at <https://aerobasegroup.com/nsn/4720-00-289-4258>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Left-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response

**Outside Diameter:**

0.594 inches

**Exterior Color:**

Red

**Connection Style:**

Swivel nut, gas 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Burst Test Pressure:**

700.0 pounds per square inch

**Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated polyamide fabric and 2nd layer rubber impregnated braided cotton cord or 2nd layer rubber impregnated polyamide fabric and outer layer molded rubber, synthetic

**Thread Size:**

0.562 inches 1st end

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches excluding end fittings

**Seat Radius:**

0.196 inches 1st end

**Special Features:**

Double braid; fitting designations (nut) cgae1hn023-000b; (tailpiece) cgae1ts022-d05b

**Special Markings:**

Capital letters/fuel/

**Media For Which Designed:**

Acetylene single response

**Thread Series Designator:**

Unf 1st end

**Specification Or Standard:**

S type and r grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0