NSN 4720-00-289-4420

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-289-4420

Round Inside Diameter: 3.000 inches first end Endlength: 1.500 inches both ends Connection Style: Round both ends Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard: 2 class and d grade and 2 type
3.000 inches first end Endlength: 1.500 inches both ends Connection Style: Round both ends Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Endlength: 1.500 inches both ends Connection Style: Round both ends Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
1.500 inches both ends Connection Style: Round both ends Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Connection Style: Round both ends Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Connection Type: Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Soft both ends End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
End Inside Diameter: 3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
3.500 inches both ends Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Maximum Operating Pressure: 20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
20.0 pounds per square inch Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Measuring Method And Length: 23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
23.500 inches Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Material: Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Steel reinforcing wire Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Style Designator: Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Helically wound continous wire supported Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
Specification Data: 81205-bacd40a professional/industrial association standard Specification Or Standard:
81205-bacd40a professional/industrial association standard Specification Or Standard:
Specification Or Standard:
2 class and digrade and 2 type
2 diass and a grade and 2 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A229a0