Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-4494

• • • • •	
Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Ratin	g:
-65.0 degrees fahrer	nheit and 160.0 degrees fahrenheit single response
Outside Diameter:	
0.516 inches	
Connection Style:	
Swivel nut flare 1st e	and
End Connection De	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Burst Test Pressur	e:
12000.0 pounds per	square inch
Layer Composition	And Location:
2nd layer braided ste	eel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operatin	g Pressure:
3000.0 pounds per s	quare inch
Thread Size:	
0.438 inches 1st end	ł
Seat Angle:	
37.0 degrees 1st en	b
Hydrostatic Test P	ressure:
6000.0 pounds per s	square inch
Vacuum In Torr:	
50.8	
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
29.500 inches work	
Thread Series Desi	-
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-00-289-4494

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0