

View Online at <https://aerobasegroup.com/nsn/4720-00-289-4560>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

0.516 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

Thread Size:

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

Outer Covering Environmental Protection:

Mildew resistant and alcohol resistant and fuel resistant and hydraulic solution resistant and oil resistant and water resistant and salt water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.750 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0