## NSN 4720-00-289-4612



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-289-4612 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 900.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided textile yarn and outer layer molded rubber, synthetic and 1st layer braided textile yarn **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 450.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

300.000 inches

**Special Features:** 

Furnished with nipple and sleeve

## NSN 4720-00-289-4612

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Air and water single response
Thread Series Designator:
Unf 1st end
Specification Data:
81349-mil-s-15297 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0