NSN 4720-00-289-6044

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-6044

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-38.0 degrees fahrenheit and 150.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Exterior Color:
Black
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal pipe 1st end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated braided rayon cord and 2nd layer rubber impregnated
braided cotton cord or 2nd layer rubber impregnated braided rayon cord and outer layer molded rubber
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Outer Covering Environmental Protection:
Light resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
96.000 inches
Special Markings:
Air-w.P150 lbs
Media For Which Designed:
Air single response

Unf 1st end

Thread Series Designator:

NSN 4720-00-289-6044

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81348-zz-h-461 government specification

Specification Or Standard:

2 type and a style and 5/16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0