## NSN 4720-00-289-6162

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-6162

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
Between 0.453 inches and 0.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided cotton cord
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and water resistant and alcohol resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches working
Media For Which Designed:

Air single response

## NSN 4720-00-289-6162

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

**Specification Data:** 

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0