NSN 4720-00-289-6299

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-6299

Cross Sectional Shape:
Round Thread Class
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pressure:
600.0 pounds per square inch
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
37.500 inches working
Media For Which Designed:
Air and fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon single response
Specification Data:
96906-ms28741 government standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-00-289-6299

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0