NSN 4720-00-289-6374

Nonmetallic Hose Assembly - Page 1 of 2

Abrasion resistant and mildew resistant and oil resistant



View Online at https://aerobasegroup.com/nsn/4720-00-289-6374

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.812 inches
Bolt Circle Diameter:
2.825 inches 2nd end
Outside Diameter:
2.219 inches
Bolt Hole Quantity:
4 1st end
Connection Style:
Swivel nut flare 1st end
Bolt Hole Diameter:
0.344 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
2.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

NSN 4720-00-289-6374

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches working
Media For Which Designed:
Air and fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: