NSN 4720-00-289-9202

Nonmetallic Hose - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-9202

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.125 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.453 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Gray or black |
| End Application: |
| Grumman a10 aircraft |
| Burst Test Pressure: |
| 12000.0 pounds per square inch single response |
| Layer Composition And Location: |
| Outer layer rubber impregnated braided cotton cord err-100 |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Material: |
| Rubber synthetic tube |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Specification Data: |
| 813491I-h-8794 government specification |
| Specification Or Standard: |
| 3 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A541z0

NSN 4720-00-289-9202

Nonmetallic Hose - Page 2 of 2



Mil-std (military Standard):

Mil-h-8794 spec.