NSN 4720-00-289-9353

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-289-9353

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.875 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 9.620 inches |
| Hose Or Tubing Specification/std Data: |
| Mil-h-8788, size 16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Second End Relationship With First End: |
| Not identical |
| Burst Test Pressure: |
| 10000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| 2nd layer braided steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 1.312 inches 2nd end |
| Seat Angle: |

Hydrostatic Test Pressure: 5000.0 pounds per square inch

37.0 degrees 2nd end

NSN 4720-00-289-9353

Nonmetallic Hose Assembly - Page 2 of 2



| Flow Angle: |
|---|
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and mildew resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 36.000 inches working |
| Second End Swivel Action Capability: |
| Not included |
| Special Features: |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Un 2nd end |
| Specification Data: |
| Mil-h-8788, size 16 professional/industrial association specification and 96906-ms28921 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| Mil-std (military Standard): |
| Mil-h-8788 spec. |