NSN 4720-00-293-7417

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-293-7417

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.562 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.031 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unf 1st end

NSN 4720-00-293-7417

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0