

View Online at <https://aerobasegroup.com/nsn/4720-00-293-7882>

Cross Sectional Shape:

Round

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 100.0 degrees fahrenheit single response

Outside Diameter:

1.469 inches

First End Fitting Specification/std Data:

Ww-c-633-04-m specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

0.750 inches 1st end

Connection Style:

Universal 1st end

End Connection Design:

Straight 1st end

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Universal quick disconnect 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

700.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Hydrostatic Test Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches excluding end fittings

Special Features:

Inner conveying tube material-rubber, synthetic

Special Markings:

Pneumatic

Media For Which Designed:

Air single response

Specification Data:

Ww-c-633-04-m professional/industrial association specification and 81348-zz-h-500 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0