Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-294-1443

Crease Sectional Shares
Cross Sectional Shape: Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end Inside Diameter:
0.375 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided synthetic cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 6.875 inches working Media For Which Designed: Air single response **Thread Series Designator:** Unjf 1st end **Specification Data:** 88044-an6270 government standard Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0