## NSN 4720-00-297-1003

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-297-1003

Cross Sectional Shape
Cross Sectional Shape:
Round
Thread Class: 2b 1st end
Thread Direction:
Right-hand 1st end Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded plastic and 1st layer braided fiber
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
48.000 inches
Special Features:
With metal sleeves 1.875 lg.
Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

## NSN 4720-00-297-1003

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0