NSN 4720-00-299-0779

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-299-0779

Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.375 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response			
Outside Diameter:			
0.781 inches			
Minimum Inside Bending Radius:			
5.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 2nd end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
18 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided steel wire and outer layer molded rubber, chloroprene			
Maximum Operating Pressure:			
2250.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Hydrostatic Test Pressure:			
4500.0 pounds per square inch			
Flow Angle:			
45.0 degrees 1st end			
Outer Covering Environmental Protection:			
Mildew resistant and oil resistant and oil resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
9.500 inches working and 10.000 inches working			
Media For Which Designed:			
Fuel/oil, hydrocarbon single response			

NSN 4720-00-299-0779

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0