NSN 4720-00-299-0885

Cross Sectional Shape:

7.000 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-299-0885

| Round | | | | |
|---|--|--|--|--|
| Thread Class: | | | | |
| 3b 1st end | | | | |
| Thread Direction: | | | | |
| Right-hand 1st end | | | | |
| Inside Diameter: | | | | |
| Between 0.477 inches and 0.570 inches | | | | |
| Tempurature Rating: | | | | |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| Between 0.718 inches and 0.789 inches | | | | |
| Minimum Inside Bending Radius: | | | | |
| 5.000 inches | | | | |
| Exterior Color: | | | | |
| Black | | | | |
| Connection Style: | | | | |
| Swivel nut, flareless 2nd end | | | | |
| End Connection Design: | | | | |
| Straight 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 1st end | | | | |
| Burst Test Pressure: | | | | |
| 1000.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| Outer layer molded rubber, synthetic and 1st layer braided fabric | | | | |
| Maximum Operating Pressure: | | | | |
| 250.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.750 inches 2nd end | | | | |
| Seat Angle: | | | | |
| 12.0 degrees 2nd end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 500.0 pounds per square inch | | | | |
| Flow Angle: | | | | |
| 90.0 degrees 2nd end | | | | |
| Outer Covering Environmental Protection: | | | | |
| Mildew resistant | | | | |
| Inside Surface Condition: | | | | |
| Smooth | | | | |
| Measuring Method And Length: | | | | |

NSN 4720-00-299-0885

Nonmetallic Hose Assembly - Page 2 of 2



| | laa a al | C! | D! | _4 |
|---|----------|--------|--------|-------|
| ı | nread | Series | Design | ator: |

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0