NSN 4720-00-299-0964

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-299-0964

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Minimum Inside Bending Radius:
5.500 inches
Angle Between Rigid Elbow Fittings In Deg:
0.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3500.0 pounds per square inch
Flow Angle:

Inside Surface Condition:

Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant

maide duridee doridit

Smooth

90.0 degrees 1st end

NSN 4720-00-299-0964

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
19.000 inches
Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0