

View Online at <https://aerobasegroup.com/nsn/4720-00-299-0968>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.656 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and reusable end fittings

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

34.000 inches working

**Special Features:**

External support hose up to hex of end fittings which have assembled in 2 polyethylene protective plugs iaw nas 815-10

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

96906-ms8000 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0