

View Online at <https://aerobasegroup.com/nsn/4720-00-301-5594>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Outside Diameter:

1.844 inches

Minimum Inside Bending Radius:

4.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-2217 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting nickel alloy 400 all ends

Connection Type:

Threaded internal hose 1st end

Second End Relationship With First End:

Not identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer helix copper coil

Thread Size:

1.000 inches 2nd end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, chloroprene; furnished with 1 washer, 4 1.000 in. Hose clamps, 1 1.000 in. Hose clamp up per, 1 1.000 in. Hose clamp lower, 2 cotter pins

Thread Series Designator:

Npsh 2nd end

Specification Data:

Mil-h-2217 professional/industrial association specification and 81349-mil-h-2217 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-2217 spec.