

View Online at <https://aerobasegroup.com/nsn/4720-00-301-5594>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.000 inches

**Outside Diameter:**

1.844 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-2217 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting nickel alloy 400 all ends

**Connection Type:**

Threaded internal hose 1st end

**Second End Relationship With First End:**

Not identical

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

2nd layer helix copper coil

**Thread Size:**

1.000 inches 2nd end

**Hydrostatic Test Pressure:**

600.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, chloroprene; furnished with 1 washer, 4 1.000 in. Hose clamps, 1 1.000 in. Hose clamp up per, 1 1.000 in. Hose clamp lower, 2 cotter pins

**Thread Series Designator:**

Npsh 2nd end

**Specification Data:**

Mil-h-2217 professional/industrial association specification and 81349-mil-h-2217 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-2217 spec.