## NSN 4720-00-303-4972

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-303-4972

Cross Sectional Shape:
Round
Inside Diameter:
3.000 inches
Tempurature Rating:
-32.0 degrees fahrenheit single response
Outside Diameter:
3.500 inches
Exterior Color:
Black
Quick Disconnect Size:
3.000 inches 1st end
Connection Style:
Cam or lever (internal) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
125.0 pounds per square inch
Hydrostatic Test Pressure:
250.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and abrasion resistant and fuel resistant and hydraulic solution resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches excluding end fittings
Special Markings:
Hose, liquid petroleum fuels, dispensing, collapsible type 1, 200 p.S.I.G. Minium burst
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:
81349-mil-h-11588 government specification

**Specification Or Standard:** 

1 type and 1 class and 3-inch size

## NSN 4720-00-303-4972

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0