NSN 4720-00-304-3463

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-304-3463 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.469 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Internal support **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided cotton cord **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant **Inside Surface Condition:**

Smooth

Measuring Method And Length:

21.000 inches

NSN 4720-00-304-3463

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0