NSN 4720-00-307-7822

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-307-7822

Cross Sectional Shape:
Round
Inside Diameter:
0.320 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.470 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Natural
Quick Disconnect Size:
0.875 inches 2nd end
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
78.000 inches
Special Features:
Both ends furnished with dust cap and plug; second has triangular shaped mtg flange w/three mtg holes 0.188 in. Dia
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No

NSN 4720-00-307-7822

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0